Membrane oxygenator - with membranes made as corrugated porous material with silicone rubber coating.

L20 ANSWER 118 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD 1983-55955K [23] WPINDEX DNC C1983-054497 DNN N1983-101111 A88 J02 P34 DC IN KARICHEV, Z R; MUCHNIK, G F (LIDO-I) LIDORENKO N S CYC SU 948386 B 19820807 (198323)* 2p PI PRAI SU 1974-2068552 19741029 1983-55955K [23] WPINDEX 948386 B UPAB: 19930925

The membrane oxygenator has a body (1) and selective membranes (2) made of corrugated porous material, e.g. metal-ceramic with a silicone rubber coating.

Venous blood passes through connection (3) into collector (4) and is evenly distributed along the flat channels of each membrane (2) of the blood flow chambers (5). At the same time oxygen or air passes through connection (6) into collector (7) and through an aperture in seal (8) into gas chambers (9), washing over membranes (2). The oxygen is diffused into the blood, saturating it, and the excess carbon dioxide is removed from the blood into the gas stream, so the venous blood is converted into arterial blood which is collected in collectors (10) and passes from connections (11) to the patient. The air and carbon dioxide mixture passes through gas chambers (9) and seal (8) second aperture into collectors (12) and through connections (13) into the atmosphere. Bul.29/7.8.82